

スペック表

品番	全長 (m)	継数 (本)	仕舞寸法 (cm)	自重 (g)	先径 (mm)	適合ルアー ウェイト(g)	適合ライン ナイロン・フロロ(lb)	適合ライン PE(号)	グリップ長(mm)	テーパー	カーボン 含有率(%)	本体価格 (円)	商品コード	
162L-BFS	1.88	1	188.0	87	1.5	3.5~10	6~12	-	205	FF	98.5	54,000	36797 6	*
166L-G	1.98	1	198.0	90	1.9	4~12	6~12	-	215	RF	85.9	55,000	36798 3	*
166L+-BFS	1.98	1	198.0	90	1.6	4~12	6~12	-	210	FF	99.7	55,000	37132 4	*
166M	1.98	1	198.0	97	1.8	7~21	8~16	-	215	RF	99.9	54,000	36799 0	*
166MH	1.98	1	198.0	97	2.0	10~30	10~20	-	220	F	99.9	55,500	36800 3	*
168ML-LM	2.03	1	203.0	97	2.0	5~18	7~14	-	240	RF	98.9	56,000	37319 9	*
追加 168M-LM	2.03	1	203.0	100	2.2	7~28	8~16	-	242	RF	100.0	57,000	38092 0	*
追加 168MH-LM	2.03	1	203.0	102	2.2	10~35	10~20	-	246	RF	100.0	58,000	38093 7	*
169XH-SB	2.06	1	206.0	117	2.3	MAX150	14~30	MAX6	255	RF	99.1	58,000	37893 4	*
1610ML-BFS	2.08	1	208.0	97	1.9	4~15	7~14	-	235	F	99.0	55,500	37133 1	*
1610M	2.08	1	208.0	102	2.0	7~21	8~16	-	242	RF	99.8	55,500	36804 1	*
1610H	2.08	1	208.0	112	2.0	12~42	12~25	MAX5	250	RF	99.0	57,000	36805 8	*
1611MH	2.11	1	211.0	112	1.9	10~30	10~20	-	246	F	99.5	56,000	36806 5	*
170H-SB	2.13	2	180.7	115	2.3	12~56	12~25	MAX5	265	RF	97.2	58,000	36807 2	*
追加 170H+	2.13	2	182.0	120	2.4	14~56	12~30	MAX5	251	F	99.4	58,500	38094 4	*
172H	2.18	2	186.4	120	2.1	12~42	12~25	MAX5	258	RF	99.5	58,000	36808 9	*
174MH	2.24	2	191.7	117	2.0	10~30	10~20	-	265	RF	99.5	58,000	36809 6	*
174XH-SB	2.24	2	188.4	135	2.3	MAX150	14~30	MAX6	298	RF	99.4	60,000	37130 0	*
176H	2.29	2	196.4	127	2.3	12~42	12~25	MAX5	268	F	99.5	59,000	36810 2	*
176XXH-SB	2.29	2	192.7	147	2.6	MAX300	16~35	MAX8	302	RF	98.9	63,000	37892 7	*