

# スペック表

品番	全長 (m)	アクション	継数 (本)	仕舞寸法 (cm)	自重 (g)	先径 (mm)	適合ルアーウェイト (g)	適合ライン ナイロン (lb) /PE (号)	リールシート位置 (mm)	カーボン含有率 (%)	本体価格 (円)	商品コード
【追加】 S43UL-4	1.30	Ultra Light	4	36.8	68	1.5	1~7	2~6/0.2~0.6	105	91.8	29,000	399281
【追加】 S48UL-4	1.42	Ultra Light	4	39.8	69	1.5	1~7	2~6/0.2~0.6	105	92.8	29,500	399298
【追加】 S54UL	1.63	Ultra Light	2	84.3	71	1.5	1~7	2~6/0.2~0.6	142	93.2	27,000	399304
【追加】 S60UL	1.83	Ultra Light	2	94.3	79	1.6	2~9	2~8/0.2~0.8	160	88.7	29,500	399311
【追加】 S64UL+	1.93	Ultra Light +	2	99.4	92	1.6	2~10	2~8/0.2~0.8	190	96.7	30,500	399328
【追加】 S64L	1.93	Light	2	99.8	96	1.7	3~14	3~8/0.3~0.8	210	94.3	30,500	399335
S77L	2.31	Light	2	119.2	121	1.8	4~18	4~12/0.4~1.0	267	96.4	33,500	399342
S83ML	2.51	Medium Light	2	129.6	139	1.9	5~26	6~16/0.6~1.5	291	95.1	36,000	399359
S86M	2.59	Medium	2	133.4	163	1.9	8~35	8~20/0.8~2.0	335	94.3	37,000	399366
【追加】 S120H-3	3.66	Heavy	3	128.1	359	2.1	14~70	12~30/1.2~3.0	517	95.5	48,000	399373
【追加】 B43UL-4	1.30	Ultra Light	4	36.8	75	1.5	1~7	2~6/0.2~0.6	136	91.8	30,000	399380
【追加】 B48UL-4	1.42	Ultra Light	4	39.8	79	1.5	1~7	2~6/0.2~0.6	136	92.8	30,500	399397
【追加】 B54UL	1.63	Ultra Light	2	84.3	76	1.5	1~7	2~6/0.2~0.6	136	93.2	28,000	399403
【追加】 B60UL	1.83	Ultra Light	2	94.3	85	1.6	2~9	2~8/0.2~0.8	156	88.7	30,500	399410
【追加】 B64L	1.93	Light	2	99.8	96	1.7	3~14	3~8/0.3~0.8	235	94.3	31,500	399427
B83ML	2.51	Medium Light	2	129.6	145	1.9	5~26	6~16/0.6~1.5	338	95.1	37,000	399434